

Radiator valve 179SN34


Series	F special
body	straight
DN	20 – 3/4"
connection	iron pipe
Handwheel	handwheel
Tail-piece	conical thread

Actuator to be coupled with radiator valve Series 179SN34


The straight body valve, Series F special, DN 3/4", code 179SN34, coupled with actuators **Series 148** and **148A** is certified in compliance with the norm **UNI EN 215**. The valve and the actuators are marked with Keymark:


Actuator Series
148

Actuator Series
148A
Technical features valve 179SN34

nominal pressure PN	10 bar
maximum admissible static pressure	10 bar
maximum differential pressure	1,5 bar
maximum temperature	110°C
q _m N	240 l/h ± 10%
hysteresis	0,6° C
differential pressure influence	0,5 °C
fluid temperature influence	1,4 °C
response time	22 minutes
minimum setting of temperature selector	8°C (anti-freezing mark *)
Kvs	2,6 ± 10 %
authority	0,91

The valve sealing can be substituted without emptying the circuit, in compliance with the norm UNI EN 215.

Actuator	Actuator set-point regulation						
	0	*	1	2	3	4	5
TYPE 148	close	8 °C	12 °C	16 °C	20 °C	24 °C	28 °C
TYPE 148A	close	8 °C	12 °C	16 °C	20 °C	24 °C	28 °C

Diagrams

